## REG SIZES









4.125"



4.5"







- PISTON 2 DISC SPRING 3 REG SEAT 4 SEAT 5 CARRIER 6 BALL 7 ADJUSTMENT SCREW
  - 1) MAXIMUM INPUT PRESSURE LIMIT IS 900PSI
  - 2) FOR OUTPUT OPERATING PRESSURES LESS THAN 200PSI ADJUST INPUT PRESSURE TO 500PSI FOR MAXIMUM PERFORMANCE.
  - 3) TURN ADJUSTMENT SCREW CLOCKWISE TO DECREASE PRESSURE UNTIL REGULATOR SHUTS OFF. REVERSE DIRECTION COUNTER CLOCKWISE TO INCREASE PRESSURE.
  - 4) FOR BEST ADJUSTMENT RESULTS, SHOOT YOUR MARKER WHILE SLOWLY TURNING SCREW COUNTER CLOCKWISE FROM THE OFF POSITION.
  - 5) ADJUST REGULATOR IN SMALL INCREMENTS UNTIL DESIRED PRESSURE OR VELOCITY IS ACHIEVED. HIGH PRESSURE PISTONS ARE AVAILABLE FOR OPERATING PRESSURES OVER 500 PSI



## WARRANTY INFO:

This Reg should give you years of flawless and consistent regulation. If by chance something should go wrong with this unit, CP will repair or replace this Reg for a period of 5 years. (Warranty only applies to the original purchaser)

Custom Products 1640 W Sunrise Blvd Gilbert, AZ 85233 (480)539 • 4820 phn (480)497 • 3273 fx

You have just purchased a REG that we believe to have the highest and most consistent flow rate of any REG on the market.

Thank You!!!